

LOW-PROFILE HEPA-VENT LOW-A

Face Velocity Range: 20-40 CFM/ft² (0.10-0.20 m/s)
 Low-Profile HEPA-Vent Module Selection Data

| CATALOG MODEL NO. | NOMINAL SIZE | STANDARD INLET DIMENSION ^{3.} | MAXIMUM CFM CAPACITY |
|-------------------|--------------|--|----------------------|
| LOW-1224-A | 12" x 24" | 6" rnd | 80 |
| LOW-1236-A | 12" x 36" | 6" rnd | 120 |
| LOW-1248-A | 12" x 48" | 6" rnd (8" rnd) | 160 |
| LOW-1260-A | 12" x 60" | 8" rnd | 200 |
| LOW-1272-A | 12" x 72" | 8" rnd | 240 |
| LOW-2424-A | 24" x 24" | 8" rnd | 160 |
| LOW-2436-A | 24" x 36" | 8" rnd | 240 |
| LOW-2448-A | 24" x 48" | 8" rnd (10" rnd) | 320 |
| LOW-2460-A | 24" x 60" | 10" rnd | 400 |
| LOW-2472-A | 24" x 72" | 10" rnd (12" rnd) | 480 |
| LOW-3636-A | 36" x 36" | 10" rnd | 360 |
| LOW-3648-A | 36" x 48" | 10" rnd (12" rnd) | 480 |
| LOW-3660-A | 36" x 60" | 12" rnd | 600 |

NOTES:

- 1 – The faceplate perforation percentage is 16% for all LOW-A models.
- 2 – Specify either a framed or wrap-around faceplate.
- 3 – Use acceptable alternate inlet size shown in parentheses for upper end of performance range (>33 CFM/ft²)

